



BIB UP SMART Top 180

SEMI-MANUAL FILLING MACHINE

BIB' UP SMART TOP 180

Filling machine for separate BIB and POUCH vacuum bags, in a range of formats

Compact and ergonomic, the BIB'UP SMART filling machine is ideal for small and medium production runs of 1.5 to 20-litre BIB and 1.5 to 3-litre POUCH vacuum bags.

The table-top BIB' UP SMART TOP 180 is fully equipped as standard and comes with a wide range of options to suit your sector of activity. It can handle 180 to 290 3L BIB bags per hour*, at high temperature, in cold chain or at ambient temperature.

The Smart solution!!

*Depending on the characteristics of the product to be filled, whether gravity or pump fed, the options chosen and the machine operator's working conditions.

Equipment complies with Machinery Directive 2006/42/CE. Conformity verified and validated by an independent body.

OPERATION AND DEGREE OF AUTOMATION

Complete filling cycle with manual and automated stages:

- **Manual operations:**
insertion of empty bag then, using an ergonomic lever arm: removal of tap, insertion of filling head into neck, launch of filling cycle
- **Automated operations:**
vacuum created in bag, filling and counting to programmed volume, nitrogen injection (if programmed)
- **Final manual operations:**
using ergonomic lever arm, repositioning of filling head, refitting and insertion of tap

Manual ejection of full bag

TEMPERATURE CONTROL

- For use in cleaning, priming and filling modes
- Controlled from the filling machine display
- Two setpoints: minimum and maximum, with programmable production halt management
- Configurable data recording and transfer on demand

A guaranteed quality-controlled filling process!

FASTER FILLING RATES

- Depending on your production needs, the BIB'UP SMART is designed to control an external pump
- STOP & GO operation for each filling cycle, managed by the filling machine's PLC
- Secure connection via servo connector
- Real optimisation is possible, ... up to 290 3L bags per hour

MORE info

Print

[Contact us](#)

Range of filling machines

SPEEDS

BIB/hour**BY GRAVITY/PUMP AL30/PUMP AL40****3 L 180 / 280 / 290****5 L 140 / 250 / 260****10 L 90 / 200 / 210****15 L 60 / 160 / 175****20 L 50 / 140 / 150****POUCH/hour****BY GRAVITY/PUMP AL30/PUMP AL40****1.5 L 170 / 260 / 270****3 L 110 / 240 / 250**

According to manufacturer's data

BIB/hour**BY GRAVITY/PUMP AL30/PUMP AL40****3 L 180 / 280 / 290****5 L 140 / 250 / 260****10 L 90 / 200 / 210****15 L 60 / 160 / 175****20 L 50 / 140 / 150****POUCH/hour**

BY GRAVITY/PUMP AL30/PUMP AL40

1.5 L

170 / 260 / 270

3 L

110 / 240 / 250

According to manufacturer's data

TECHNICAL CHARACTERISTICS

- Electricity supply: 230 VAC 50 Hz 1P+N+E
 - Compressed air pressure required: 6 bar
 - Nitrogen pressure required: 0,5 bar
 - Liquid infeed connection: to be defined (40 DIN as standard)
 - Dimensions: Depth: 900 mm / Height: 800 mm / Width: 640 mm
 - Weight: 30 kg (without options)
- Electricity supply: 230 VAC 50 Hz 1P+N+E
 - Compressed air pressure required: 6 bar
 - Nitrogen pressure required: 0,5 bar
 - Liquid infeed connection: to be defined (40 DIN as standard)
 - Dimensions: Depth: 900 mm / Height: 800 mm / Width: 640 mm
 - Weight: 30 kg (without options)

STANDARD CONFIGURATION – STANDARD EQUIPMENT

- Work surface: 304 stainless steel, tilt adjustable
 - 316 stainless steel liquid circuit for continuous use up to 90°C
 - No pump, 40 DIN **connection**
 - 316 stainless steel filling head with integral closure and screw-on nozzle, integrated vacuum and nitrogen-injection circuits
 - Programmable and automated CIP circuit
 - Immobiliser
 - Automatic locking of arm in filling position
 - Paddle-wheel flowmeter with 316 stainless steel body
 - Monochrome display, programme loaded via micro USB cable. A configurable recipe for each filling volume, up to 6 recipes
 - T1 mechanical clamp for Vitop or equivalent taps, high-neck
 - Options: please consult us
- Work surface: 304 stainless steel, tilt adjustable
 - 316 stainless steel liquid circuit for continuous use up to 90°C
 - No pump, 40 DIN **connection**
 - 316 stainless steel filling head with integral closure and screw-on nozzle, integrated vacuum and nitrogen-injection circuits
 - Programmable and automated CIP circuit
 - Immobiliser
 - Automatic locking of arm in filling position
 - Paddle-wheel flowmeter with 316 stainless steel body
 - Monochrome display, programme loaded via micro USB cable. A configurable recipe for each filling volume, up to 6 recipes
 - T1 mechanical clamp for Vitop or equivalent taps, high-neck
 - Options: please consult us